

Kugelhahn K182

Messing vernickelt

3-Wege Kugelhahn mit Aluminium Handgriff.



Art. Nr.	Material	Gewinde Anschluss	Einbaulänge	Mat. Dichtung	Max. Betriebsdruck 20°C	Max. temp.	Min. Mediumtemp
4401607	Messing vernickelt	1/4" bi.dr.	37 mm	PTFE	16 bar	150 °C	-30 °C
4401608	Messing vernickelt	3/8" bi.dr.	48 mm	PTFE	16 bar	150 °C	-30 °C
4401601	Messing vernickelt	1/2" bi.dr.	57 mm	PTFE	16 bar	150 °C	-30 °C
4401602	Messing vernickelt	3/4" bi.dr.	66 mm	PTFE	16 bar	150 °C	-30 °C
4401603	Messing vernickelt	1" bi.dr.	80 mm	PTFE	16 bar	150 °C	-30 °C
4401604	Messing vernickelt	1 1/4" di.dr.	92 mm	PTFE	16 bar	150 °C	-30 °C
4401605	Messing vernickelt	1 1/2" bi.dr.	105 mm	PTFE	16 bar	150 °C	-30 °C
4401606	Messing vernickelt	2" bi.dr.	122 mm	PTFE	16 bar	150 °C	-30 °C