

## KAMLOK Typ C Aluminium

Kupplung Schlauchtülle.



| Art. Nr. | Material  | Kupplungs Mass Tülle |        | Max. Betriebsdruck bei 20°C | Mat. Dichtung | Norm        |
|----------|-----------|----------------------|--------|-----------------------------|---------------|-------------|
| 4620021  | Aluminium | DN 15                | 13 mm  | 11 bar                      | NBR           | MIL-C-27487 |
| 4620022  | Aluminium | DN 20                | 19 mm  | 18 bar                      | NBR           | MIL-C-27487 |
| 4620023  | Aluminium | DN 25                | 25 mm  | 18 bar                      | NBR           | MIL-C-27487 |
| 4620025  | Aluminium | DN 32                | 32 mm  | 18 bar                      | NBR           | MIL-C-27487 |
| 4620024  | Aluminium | DN 40                | 38 mm  | 18 bar                      | NBR           | MIL-C-27487 |
| 4620026  | Aluminium | DN 50                | 50 mm  | 18 bar                      | NBR           | MIL-C-27487 |
| 4620027  | Aluminium | DN 65                | 65 mm  | 11 bar                      | NBR           | MIL-C-27487 |
| 4620028  | Aluminium | DN 75                | 75 mm  | 9 bar                       | NBR           | MIL-C-27487 |
| 4620029  | Aluminium | DN 100               | 100 mm | 7 bar                       | NBR           | MIL-C-27487 |
| 4620030  | Aluminium | DN 125               | 125 mm | 5 bar                       | NBR           | MIL-C-27487 |
| 4620031  | Aluminium | DN 150               | 150 mm | 5 bar                       | NBR           | MIL-C-27487 |